microSpire

DESIGN SPECIFICATION DATA

Sales Engineer :
Reference :
Date :

Company Name : **Contact :**

Product PT-NR : **Project :** **Yearly Quantities :**

SIGNAL TRANSFORMERS

Market : ☐ AIRSPACE ☐ AVIONICS / DEFENCE ☐ RAILWAY SYSTEMS
☐ Other : ☐ TELECOM ☐ INDUSTRY ☐ AUTOMOTIVE ☐ CONSUMER

Environment : Vibrations and/or shocks : Acceleration :
Humidity : Operating T° : Min/Max Storage T° : Min/Max

Applied Standards :

Application : ☐ AUDIO TRANSFORMER ☐ Other :

Primary Voltage : Vrms Min : Vrms Max :

Secondary Characteristics :

Output power range : THD+N : (dB) Working frequency : Bandwidth :

Output voltage (V_{AC} RMS) : Vs 1 Vs 2 Vs 3 Vs 4
Output current (A_{AC} RMS) : Is 1 Is 2 Is 3 Is 4

Shield : Prim. / Sec. : Sec. / Sec. :

Isolation : Prim. / Sec. : Sec. / Sec. :
Windings / Shields : Windings / Ground :

Maximum Dimensions : Length : Width : Height :

Report Mode : ☐ SMD ☐ THROUGH-HOLE ☐ WIRES ☐ Other :

Finish : ☐ Box ☐ Gravity molding ☐ Transfer molding ☐ Coating
☐ None ☐ Dip impregnation ☐ Vacuum Impregnation ☐ Injection

Marking : **Sticker on Packing :**

Packing : ☐ LOOSE ☐ STICK ☐ REEL ☐ TRAY ☐ UNITARY

MECHANICAL DRAWING

LAYOUT

IQ04/01/05a

Please return by fax this completely filled document at : +33.3.82.51.00.49